



FACOM 440.XSLSU - SLS Tethered Inch
Combination Spanner

440.1/4SLS, 440.5/16SLS, 440.11/32SLS, 440.3/8SLS,
440.7/16SLS, 440.1/2SLS, 440.9/16SLS, 440.5/8SLS,
440.11/16SLS, 440.3/4SLS, 440.13/16SLS, 440.7/8SLS,
440.15/16SLS, 440.1PSLS, 440.1P1/16SLS, 440.1P1/8SLS,
440.1P1/4SLS, 440.1P5/16SLS

PRODUCT NAME	CODE	SIZE
FACOM 440.1/4SLS - 1/4" SLS Tethered Inch Combination Spanner	440.1/4SLS	1/4"
FACOM 440.5/16SLS - 5/16" SLS Tethered Inch Combination Spanner	440.5/16SLS	5/16"
FACOM 440.11/32SLS - 11/32" SLS Tethered Inch Combination Spanner	440.11/32SLS	11/32"
FACOM 440.3/8SLS - 3/8" SLS Tethered Inch Combination Spanner	440.3/8SLS	3/8"
FACOM 440.7/16SLS - 7/16" SLS Tethered Inch Combination Spanner	440.7/16SLS	7/16"

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.1/2SLS - 1/2" SLS Tethered Inch Combination Spanner</u>	440.1/2SLS	1/2"
<u>FACOM 440.9/16SLS - 9/16" SLS Tethered Inch Combination Spanner</u>	440.9/16SLS	9/16"
<u>FACOM 440.5/8SLS - 5/8" SLS Tethered Inch Combination Spanner</u>	440.5/8SLS	5/8"
<u>FACOM 440.11/16SLS - 11/16" SLS Tethered Inch Combination Spanner</u>	440.11/16SLS	11/16"
<u>FACOM 440.3/4SLS - 3/4" SLS Tethered Inch Combination Spanner</u>	440.3/4SLS	3/4"
<u>FACOM 440.13/16SLS - 13/16" SLS Tethered Inch Combination Spanner</u>	440.13/16SLS	13/16"
<u>FACOM 440.7/8SLS - 7/8" SLS Tethered Inch Combination Spanner</u>	440.7/8SLS	7/8"
<u>FACOM 440.15/16SLS - 15/16" SLS Tethered Inch Combination Spanner</u>	440.15/16SLS	15/16"
<u>FACOM 440.1PSLS - 1" SLS Tethered Inch Combination Spanner</u>	440.1PSLS	1"
<u>FACOM 440.1P1/16SLS - 1.1/16" SLS Tethered Inch Combination Spanner</u>	440.1P1/16SLS	1.1/16"
<u>FACOM 440.1P1/8SLS - 1.1/8" SLS Tethered Inch Combination Spanner</u>	440.1P1/8SLS	1.1/8"

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.1P1/4SLS - 1.1/4"</u> <u>SLS Tethered Inch Combination</u> <u>Spanner</u>	440.1P1/4SLS	1.1/4"
<u>FACOM 440.1P5/16SLS - 1.5/16"</u> <u>SLS Tethered Inch Combination</u> <u>Spanner</u>	440.1P5/16SLS	1.5/16"

DESCRIPTION

FACOM 440.XSLSU - SLS Tethered Inch Combination Spanner

Features

Tool equipped with a FACOM SLS attachment solution preventing any risk of accidental falls
The crimped sliding cable solution selected and tested by FACOM maintains user ergonomics
Standard wrench for all current applications
High mechanical strength combined with compact size meeting aeronautical standards

Ring head

Ring open end (size E) designed for better access to series or embedded screws
OGV profile with 12-point ring for powerful tightening while protecting the nut
Ring head angled at 15'

Open end head

Open end angled at 15'
Open end head-handle geometry optimised for increased access

Inch sizes - 1/4 - 1"5/16

Satin chrome finish

Technical Conformity

ASME B107.100