



FACOM 440.XSLSM - SLS Tethered Metric Combination Spanner

440.6SLS, 440.7SLS, 440.8SLS, 440.9SLS, 440.10SLS, 440.11SLS, 440.12SLS, 440.13SLS, 440.14SLS, 440.15SLS, 440.16SLS, 440.17SLS, 440.18SLS, 440.19SLS, 440.21SLS, 440.22SLS, 440.23SLS, 440.24SLS, 440.27SLS, 440.29SLS, 440.30SLS, 440.32SLS, 440.34SLS

PRODUCT NAME	CODE	SIZE
FACOM 440.6SLS - 6mm SLS Tethered Metric Combination Spanner	440.6SLS	6mm
FACOM 440.7SLS - 7mm SLS Tethered Metric Combination Spanner	440.7SLS	7mm
FACOM 440.8SLS - 8mm SLS Tethered Metric Combination Spanner	440.8SLS	8mm
FACOM 440.9SLS - 9mm SLS Tethered Metric Combination Spanner	440.9SLS	9mm
FACOM 440.10SLS - 10mm SLS Tethered Metric Combination Spanner	440.10SLS	10mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.11SLS - 11mm SLS Tethered Metric Combination Spanner</u>	440.11SLS	11mm
<u>FACOM 440.12SLS - 12mm SLS Tethered Metric Combination Spanner</u>	440.12SLS	12mm
<u>FACOM 440.13SLS - 13mm SLS Tethered Metric Combination Spanner</u>	440.13SLS	13mm
<u>FACOM 440.14SLS - 14mm SLS Tethered Metric Combination Spanner</u>	440.14SLS	14mm
<u>FACOM 440.15SLS - 15mm SLS Tethered Metric Combination Spanner</u>	440.15SLS	15mm
<u>FACOM 440.16SLS - 16mm SLS Tethered Metric Combination Spanner</u>	440.16SLS	16mm
<u>FACOM 440.17SLS - 17mm SLS Tethered Metric Combination Spanner</u>	440.17SLS	17mm
<u>FACOM 440.18SLS - 18mm SLS Tethered Metric Combination Spanner</u>	440.18SLS	18mm
<u>FACOM 440.19SLS - 19mm SLS Tethered Metric Combination Spanner</u>	440.19SLS	19mm
<u>FACOM 440.21SLS - 21mm SLS Tethered Metric Combination Spanner</u>	440.21SLS	21mm
<u>FACOM 440.22SLS - 22mm SLS Tethered Metric Combination Spanner</u>	440.22SLS	22mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.23SLS - 23mm SLS Tethered Metric Combination Spanner</u>	440.23SLS	23mm
<u>FACOM 440.24SLS - 24mm SLS Tethered Metric Combination Spanner</u>	440.24SLS	24mm
<u>FACOM 440.27SLS - 27mm SLS Tethered Metric Combination Spanner</u>	440.27SLS	27mm
<u>FACOM 440.29SLS - 29mm SLS Tethered Metric Combination Spanner</u>	440.29SLS	29mm
<u>FACOM 440.30SLS - 30mm SLS Tethered Metric Combination Spanner</u>	440.30SLS	30mm
<u>FACOM 440.32SLS - 32mm SLS Tethered Metric Combination Spanner</u>	440.32SLS	32mm
<u>FACOM 440.34SLS - 34mm SLS Tethered Metric Combination Spanner</u>	440.34SLS	34mm

DESCRIPTION

FACOM 440.XSLSM - SLS Tethered Metric Combination Spanner

Features

Tool equipped with a FACOM SLS attachment solution preventing any risk of accidental falls
The crimped sliding cable solution selected and tested by FACOM maintains user ergonomics (8 - 30mm wrenches)

Standard wrench for all current applications

High mechanical strength combined with compact size meeting aeronautical standards

Ring head

Ring open end (size E) designed for better access to series or embedded screws

OGV profile with 12-point ring for powerful tightening while protecting the nut

Ring head angled at 15°

Open end head

Open end angled at 15°

Open end head-handle geometry optimised for increased access

Metric sizes - 6 - 34mm

Satin chrome finish

Technical Conformity

NF ISO 691 - NF ISO 7738 - NF ISO 3318 - NF ISO 1711-1 - E74-306 - ISO 691 - ISO 7738 - ISO 3318
- ISO 1711-1 - DIN ISO 691 - DIN 1711-1 - DIN 3113 - ASME B107.100