



## FACOM WFX.XSR - Non-Sparking Engineers Wedge



WF80.13SR, WF135.50SR, WF150.40SR, WF150.30SR,  
WF180.32SR, WF180.50SR, WF200.20SR, WF200.40SR,  
WF230.40SR, WF250.40SR

PRODUCT NAME	CODE	SIZE
<a href="#"><u>FACOM WF80.13SR - 13x80 x 6mm Non-Sparking Engineers Wedge</u></a>	WF80.13SR	13x80 x 6mm
<a href="#"><u>FACOM WF135.50SR - 50x135 x 18mm Non-Sparking Engineers Wedge</u></a>	WF135.50SR	50x135 x 18mm
<a href="#"><u>FACOM WF150.40SR - 40x150 x 8mm Non-Sparking Engineers Wedge</u></a>	WF150.40SR	40x150 x 8mm
<a href="#"><u>FACOM WF150.30SR - 30x150 x 13mm Non-Sparking Engineers Wedge</u></a>	WF150.30SR	30x150 x 13mm
<a href="#"><u>FACOM WF180.32SR - 32x180 x 13mm Non-Sparking Engineers Wedge</u></a>	WF180.32SR	32x180 x 13mm

PRODUCT NAME	CODE	SIZE
<a href="#"><u>FACOM WF180.50SR - 50x180 x 19mm Non-Sparking Engineers Wedge</u></a>	WF180.50SR	50x180 x 19mm
<a href="#"><u>FACOM WF200.20SR - 20x200 x 30mm Non-Sparking Engineers Wedge</u></a>	WF200.20SR	20x200 x 30mm
<a href="#"><u>FACOM WF200.40SR - 40x200 x 40mm Non-Sparking Engineers Wedge</u></a>	WF200.40SR	40x200 x 40mm
<a href="#"><u>FACOM WF230.40SR - 40x230 x 20mm Non-Sparking Engineers Wedge</u></a>	WF230.40SR	40x230 x 20mm
<a href="#"><u>FACOM WF250.40SR - 40x250 x 30mm Non-Sparking Engineers Wedge</u></a>	WF250.40SR	40x250 x 30mm

## DESCRIPTION

FACOM WFX.XSR - Non-Sparking Engineers Wedge

### Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions