



FACOM WFX.XSR - Non-Sparking Engineers Wedge



WF80.13SR, WF135.50SR, WF150.40SR, WF150.30SR,
WF180.32SR, WF180.50SR, WF200.20SR, WF200.40SR,
WF230.40SR, WF250.40SR

| PRODUCT NAME | CODE | SIZE |
|--|------------|---------------|
| <u>FACOM WF80.13SR - 13x80 x 6mm Non-Sparking Engineers Wedge</u> | WF80.13SR | 13x80 x 6mm |
| <u>FACOM WF135.50SR - 50x135 x 18mm Non-Sparking Engineers Wedge</u> | WF135.50SR | 50x135 x 18mm |
| <u>FACOM WF150.40SR - 40x150 x 8mm Non-Sparking Engineers Wedge</u> | WF150.40SR | 40x150 x 8mm |
| <u>FACOM WF150.30SR - 30x150 x 13mm Non-Sparking Engineers Wedge</u> | WF150.30SR | 30x150 x 13mm |
| <u>FACOM WF180.32SR - 32x180 x 13mm Non-Sparking Engineers Wedge</u> | WF180.32SR | 32x180 x 13mm |

| PRODUCT NAME | CODE | SIZE |
|--|------------|---------------|
| <u>FACOM WF180.50SR - 50x180 x 19mm Non-Sparking Engineers Wedge</u> | WF180.50SR | 50x180 x 19mm |
| <u>FACOM WF200.20SR - 20x200 x 30mm Non-Sparking Engineers Wedge</u> | WF200.20SR | 20x200 x 30mm |
| <u>FACOM WF200.40SR - 40x200 x 40mm Non-Sparking Engineers Wedge</u> | WF200.40SR | 40x200 x 40mm |
| <u>FACOM WF230.40SR - 40x230 x 20mm Non-Sparking Engineers Wedge</u> | WF230.40SR | 40x230 x 20mm |
| <u>FACOM WF250.40SR - 40x250 x 30mm Non-Sparking Engineers Wedge</u> | WF250.40SR | 40x250 x 30mm |

DESCRIPTION

FACOM WFX.XSR - Non-Sparking Engineers Wedge

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions