



FACOM 265.263.XSR - Non-Sparking Engineers Chisel



265.20SR, 265.22SR, 265.24SR, 265.26SR, 265.28SR, 265.29SR, 263.30SR, 263.32SR

PRODUCT NAME	CODE	SIZE
FACOM 265.20SR - 12x150mm Non-Sparking Engineers Chisel	265.20SR	12x150mm
FACOM 265.22SR - 14x160mm Non-Sparking Engineers Chisel	265.22SR	14x160mm
FACOM 265.24SR - 16x200mm Non-Sparking Engineers Chisel	265.24SR	16x200mm
FACOM 265.26SR - 18x160mm Non-Sparking Engineers Chisel	265.26SR	18x160mm
FACOM 265.28SR - 19x350mm Non-Sparking Engineers Chisel	265.28SR	19x350mm
FACOM 265.29SR - 24x600mm Non-Sparking Engineers Chisel	265.29SR	24x600mm
FACOM 263.30SR - 28x300mm Non-Sparking Engineers Chisel	263.30SR	28x300mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 263.32SR - 35x300mm Non-Sparking Engineers Chisel</u>	263.32SR	35x300mm

DESCRIPTION

FACOM 265.263.XSR - Non-Sparking Engineers Chisel

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions