



FACOM 249.XSR - Non-Sparking Parallel Drift Punch



249.3SR, 249.4SR, 249.6SR, 249.8SR, 249.10SR, 249.12SR

PRODUCT NAME	CODE	SIZE
FACOM 249.3SR - 3mm Non-Sparking Parallel Drift Punch	249.3SR	3mm
FACOM 249.4SR - 4mm Non-Sparking Parallel Drift Punch	249.4SR	4mm
FACOM 249.6SR - 6mm Non-Sparking Parallel Drift Punch	249.6SR	6mm
FACOM 249.8SR - 8mm Non-Sparking Parallel Drift Punch	249.8SR	8mm
FACOM 249.10SR - 10mm Non-Sparking Parallel Drift Punch	249.10SR	10mm
FACOM 249.12SR - 12mm Non-Sparking Parallel Drift Punch	249.12SR	12mm

DESCRIPTION

FACOM 249.XSR - Non-Sparking Parallel Drift Punch

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions