



FACOM M.XSRM - Non-Sparking 1" Square Drive Metric 12pt Socket

M.30SR, M.32SR, M.34SR, M.36SR, M.38SR, M.41SR, M.46SR, M.50SR, M.55SR, M.60SR, M.65SR, M.70SR, M.75SR

PRODUCT NAME	CODE	SIZE
FACOM M.30SR - 30mm Non-Sparking 1" Square Drive Metric 12pt Socket	M.30SR	30mm
FACOM M.32SR - 32mm Non-Sparking 1" Square Drive Metric 12pt Socket	M.32SR	32mm
FACOM M.34SR - 34mm Non-Sparking 1" Square Drive Metric 12pt Socket	M.34SR	34mm
FACOM M.36SR - 36mm Non-Sparking 1" Square Drive Metric 12pt Socket	M.36SR	36mm
FACOM M.38SR - 38mm Non-Sparking 1" Square Drive Metric 12pt Socket	M.38SR	38mm

PRODUCT NAME	CODE	SIZE
<u>FACOM M.41SR - 41mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.41SR	41mm
<u>FACOM M.46SR - 46mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.46SR	46mm
<u>FACOM M.50SR - 50mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.50SR	50mm
<u>FACOM M.55SR - 55mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.55SR	55mm
<u>FACOM M.60SR - 60mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.60SR	60mm
<u>FACOM M.65SR - 65mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.65SR	65mm
<u>FACOM M.70SR - 70mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.70SR	70mm
<u>FACOM M.75SR - 75mm Non-Sparking 1" Square Drive Metric 12pt Socket</u>	M.75SR	75mm

DESCRIPTION

FACOM M.XSRM - Non-Sparking 1" Square Drive Metric 12pt Socket

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Drive - 1"

Metric sizes - 30 - 75mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions