



FACOM K.XSRM - Non-Sparking 3/4" Square Drive Metric 12pt Socket

K.17SR, K.19SR, K.21SR, K.22SR, K.23SR, K.24SR, K.26SR, K.27SR, K.28SR, K.29SR, K.30SR, K.32SR, K.34SR, K.36SR, K.38SR, K.41SR, K.46SR, K.50SR

PRODUCT NAME	CODE	SIZE
FACOM K.17SR - 17mm Non-Sparking 3/4" Square Drive Metric 12pt Socket	K.17SR	17mm
FACOM K.19SR - 19mm Non-Sparking 3/4" Square Drive Metric 12pt Socket	K.19SR	19mm
FACOM K.21SR - 21mm Non-Sparking 3/4" Square Drive Metric 12pt Socket	K.21SR	21mm
FACOM K.22SR - 22mm Non-Sparking 3/4" Square Drive Metric 12pt Socket	K.22SR	22mm
FACOM K.23SR - 23mm Non-Sparking 3/4" Square Drive Metric 12pt Socket	K.23SR	23mm

PRODUCT NAME	CODE	SIZE
<u>FACOM K.24SR - 24mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.24SR	24mm
<u>FACOM K.26SR - 26mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.26SR	26mm
<u>FACOM K.27SR - 27mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.27SR	27mm
<u>FACOM K.28SR - 28mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.28SR	28mm
<u>FACOM K.29SR - 29mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.29SR	29mm
<u>FACOM K.30SR - 30mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.30SR	30mm
<u>FACOM K.32SR - 32mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.32SR	32mm
<u>FACOM K.34SR - 34mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.34SR	34mm
<u>FACOM K.36SR - 36mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.36SR	36mm
<u>FACOM K.38SR - 38mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.38SR	38mm
<u>FACOM K.41SR - 41mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.41SR	41mm

PRODUCT NAME	CODE	SIZE
<u>FACOM K.46SR - 46mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.46SR	46mm
<u>FACOM K.50SR - 50mm Non-Sparking 3/4" Square Drive Metric 12pt Socket</u>	K.50SR	50mm

DESCRIPTION

FACOM K.XSRM - Non-Sparking 3/4" Square Drive Metric 12pt Socket

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Drive - 3/4"

Metric sizes - 17 - 50mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions