



FACOM S.XSRM - Non-Sparking 1/2" Square Drive Metric 12pt Socket

S.6SR, S.7SR, S.8SR, S.9SR, S.10SR, S.11SR, S.12SR, S.13SR, S.14SR, S.15SR, S.16SR, S.17SR, S.18SR, S.19SR, S.20SR, S.21SR, S.22SR, S.23SR, S.24SR, S.25SR, S.26SR, S.27SR, S.28SR, S.29SR, S.30SR, S.32SR

PRODUCT NAME	CODE	SIZE
FACOM S.6SR - 6mm Non-Sparking 1/2" Square Drive Metric 12pt Socket	S.6SR	6mm
FACOM S.7SR - 7mm Non-Sparking 1/2" Square Drive Metric 12pt Socket	S.7SR	7mm
FACOM S.8SR - 8mm Non-Sparking 1/2" Square Drive Metric 12pt Socket	S.8SR	8mm
FACOM S.9SR - 9mm Non-Sparking 1/2" Square Drive Metric 12pt Socket	S.9SR	9mm
FACOM S.10SR - 10mm Non-Sparking 1/2" Square Drive Metric 12pt Socket	S.10SR	10mm

PRODUCT NAME	CODE	SIZE
<u>FACOM S.11SR - 11mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.11SR	11mm
<u>FACOM S.12SR - 12mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.12SR	12mm
<u>FACOM S.13SR - 13mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.13SR	13mm
<u>FACOM S.14SR - 14mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.14SR	14mm
<u>FACOM S.15SR - 15mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.15SR	15mm
<u>FACOM S.16SR - 16mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.16SR	16mm
<u>FACOM S.17SR - 17mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.17SR	17mm
<u>FACOM S.18SR - 18mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.18SR	18mm
<u>FACOM S.19SR - 19mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.19SR	19mm
<u>FACOM S.20SR - 20mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.20SR	20mm
<u>FACOM S.21SR - 21mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.21SR	21mm

PRODUCT NAME	CODE	SIZE
<u>FACOM S.22SR - 22mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.22SR	22mm
<u>FACOM S.23SR - 23mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.23SR	23mm
<u>FACOM S.24SR - 24mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.24SR	24mm
<u>FACOM S.25SR - 25mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.25SR	25mm
<u>FACOM S.26SR - 26mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.26SR	26mm
<u>FACOM S.27SR - 27mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.27SR	27mm
<u>FACOM S.28SR - 28mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.28SR	28mm
<u>FACOM S.29SR - 29mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.29SR	29mm
<u>FACOM S.30SR - 30mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.30SR	30mm
<u>FACOM S.32SR - 32mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u>	S.32SR	32mm

DESCRIPTION

FACOM S.XSRM - Non-Sparking 1/2" Square Drive Metric 12pt Socket

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Drive - 1/2"

Metric sizes - 6 - 32mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions