



## FACOM S.XSRM - Non-Sparking 1/2" Square Drive Metric 12pt Socket

S.6SR, S.7SR, S.8SR, S.9SR, S.10SR, S.11SR, S.12SR, S.13SR, S.14SR, S.15SR, S.16SR, S.17SR, S.18SR, S.19SR, S.20SR, S.21SR, S.22SR, S.23SR, S.24SR, S.25SR, S.26SR, S.27SR, S.28SR, S.29SR, S.30SR, S.32SR

| PRODUCT NAME                                                                          | CODE   | SIZE |
|---------------------------------------------------------------------------------------|--------|------|
| <a href="#">FACOM S.6SR - 6mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</a>   | S.6SR  | 6mm  |
| <a href="#">FACOM S.7SR - 7mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</a>   | S.7SR  | 7mm  |
| <a href="#">FACOM S.8SR - 8mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</a>   | S.8SR  | 8mm  |
| <a href="#">FACOM S.9SR - 9mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</a>   | S.9SR  | 9mm  |
| <a href="#">FACOM S.10SR - 10mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</a> | S.10SR | 10mm |

| PRODUCT NAME                                                                                 | CODE   | SIZE |
|----------------------------------------------------------------------------------------------|--------|------|
| <a href="#"><u>FACOM S.11SR - 11mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.11SR | 11mm |
| <a href="#"><u>FACOM S.12SR - 12mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.12SR | 12mm |
| <a href="#"><u>FACOM S.13SR - 13mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.13SR | 13mm |
| <a href="#"><u>FACOM S.14SR - 14mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.14SR | 14mm |
| <a href="#"><u>FACOM S.15SR - 15mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.15SR | 15mm |
| <a href="#"><u>FACOM S.16SR - 16mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.16SR | 16mm |
| <a href="#"><u>FACOM S.17SR - 17mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.17SR | 17mm |
| <a href="#"><u>FACOM S.18SR - 18mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.18SR | 18mm |
| <a href="#"><u>FACOM S.19SR - 19mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.19SR | 19mm |
| <a href="#"><u>FACOM S.20SR - 20mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.20SR | 20mm |
| <a href="#"><u>FACOM S.21SR - 21mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.21SR | 21mm |

| PRODUCT NAME                                                                                 | CODE   | SIZE |
|----------------------------------------------------------------------------------------------|--------|------|
| <a href="#"><u>FACOM S.22SR - 22mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.22SR | 22mm |
| <a href="#"><u>FACOM S.23SR - 23mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.23SR | 23mm |
| <a href="#"><u>FACOM S.24SR - 24mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.24SR | 24mm |
| <a href="#"><u>FACOM S.25SR - 25mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.25SR | 25mm |
| <a href="#"><u>FACOM S.26SR - 26mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.26SR | 26mm |
| <a href="#"><u>FACOM S.27SR - 27mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.27SR | 27mm |
| <a href="#"><u>FACOM S.28SR - 28mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.28SR | 28mm |
| <a href="#"><u>FACOM S.29SR - 29mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.29SR | 29mm |
| <a href="#"><u>FACOM S.30SR - 30mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.30SR | 30mm |
| <a href="#"><u>FACOM S.32SR - 32mm Non-Sparking 1/2" Square Drive Metric 12pt Socket</u></a> | S.32SR | 32mm |

---

## DESCRIPTION

FACOM S.XSRM - Non-Sparking 1/2" Square Drive Metric 12pt Socket

### Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Drive - 1/2"

Metric sizes - 6 - 32mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions