



FACOM 49.XSRM - Non-Sparking Metric Impact Slogging Open Jaw Spanner

49.17SR, 49.19SR, 49.22SR, 49.24SR, 49.27SR, 49.30SR, 49.32SR, 49.36SR, 49.41SR, 49.46SR, 49.50SR, 49.55SR, 49.60SR, 49.65SR, 49.70SR, 49.75SR, 49.80SR, 49.85SR, 49.90SR, 49.95SR, 49.100SR, 49.105SR, 49.110SR, 49.120SR, 49.130SR

PRODUCT NAME	CODE	SIZE
<u>FACOM 49.17SR - 17mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.17SR	17mm
<u>FACOM 49.19SR - 19mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.19SR	19mm
<u>FACOM 49.22SR - 22mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.22SR	22mm
<u>FACOM 49.24SR - 24mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.24SR	24mm
<u>FACOM 49.27SR - 27mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.27SR	27mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 49.30SR - 30mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.30SR	30mm
<u>FACOM 49.32SR - 32mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.32SR	32mm
<u>FACOM 49.36SR - 36mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.36SR	36mm
<u>FACOM 49.41SR - 41mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.41SR	41mm
<u>FACOM 49.46SR - 46mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.46SR	46mm
<u>FACOM 49.50SR - 50mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.50SR	50mm
<u>FACOM 49.55SR - 55mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.55SR	55mm
<u>FACOM 49.60SR - 60mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.60SR	60mm
<u>FACOM 49.65SR - 65mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.65SR	65mm
<u>FACOM 49.70SR - 70mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.70SR	70mm
<u>FACOM 49.75SR - 75mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.75SR	75mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 49.80SR - 80mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.80SR	80mm
<u>FACOM 49.85SR - 85mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.85SR	85mm
<u>FACOM 49.90SR - 90mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.90SR	90mm
<u>FACOM 49.95SR - 95mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.95SR	95mm
<u>FACOM 49.100SR - 100mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.100SR	100mm
<u>FACOM 49.105SR - 105mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.105SR	105mm
<u>FACOM 49.110SR - 110mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.110SR	110mm
<u>FACOM 49.120SR - 120mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.120SR	120mm
<u>FACOM 49.130SR - 130mm Non-Sparking Metric Impact Slogging Open Jaw Spanner</u>	49.130SR	130mm

DESCRIPTION

FACOM 49.XSRM - Non-Sparking Metric Impact Slogging Open Jaw Spanner

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Metric sizes - 17 - 130mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions