



FACOM 50.XSRU - Non-Sparking Inch Impact Slogging Ring Spanner

50.11/16SR, 50.3/4SR, 50.7/8SR, 50.1PSR, 50.1P1/16SR, 50.1P1/8SR, 50.1P3/16SR, 50.1P1/4SR, 50.1P3/8SR, 50.1P1/2SR, 50.1P5/8SR, 50.1P3/4SR, 50.1P13/16SR, 50.2PSR, 50.2P1/16SR, 50.2P3/16SR, 50.2P13/64SR, 50.2P3/8SR, 50.2P9/16SR, 50.2P5/8SR, 50.2P3/4SR, 50.2P15/16SR, 50.3PSR, 50.3P1/8SR, 50.3P3/8SR, 50.3P9/16SR, 50.3P3/4SR, 50.3P15/16SR, 50.4P1/8SR

PRODUCT NAME	CODE	SIZE
FACOM 50.11/16SR - 11/16" Non-Sparking Inch Impact Slogging Ring Spanner	50.11/16SR	11/16"
FACOM 50.3/4SR - 3/4" Non-Sparking Inch Impact Slogging Ring Spanner	50.3/4SR	3/4"
FACOM 50.7/8SR - 7/8" Non-Sparking Inch Impact Slogging Ring Spanner	50.7/8SR	7/8"
FACOM 50.1PSR - 1" Non-Sparking Inch Impact Slogging Ring Spanner	50.1PSR	1"
FACOM 50.1P1/16SR - 1.1/16" Non-Sparking Inch Impact Slogging Ring Spanner	50.1P1/16SR	1.1/16"

PRODUCT NAME	CODE	SIZE
<u>FACOM 50.1P1/8SR - 1.1/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P1/8SR	1.1/8"
<u>FACOM 50.1P3/16SR - 1.3/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P3/16SR	1.3/16"
<u>FACOM 50.1P1/4SR - 1.1/4"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P1/4SR	1.1/4"
<u>FACOM 50.1P3/8SR - 1.3/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P3/8SR	1.3/8"
<u>FACOM 50.1P1/2SR - 1.1/2"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P1/2SR	1.1/2"
<u>FACOM 50.1P5/8SR - 1.5/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P5/8SR	1.5/8"
<u>FACOM 50.1P3/4SR - 1.3/4"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P3/4SR	1.3/4"
<u>FACOM 50.1P13/16SR - 1.13/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.1P13/16SR	1.13/16"
<u>FACOM 50.2PSR - 2" Non-Sparking Inch Impact Slogging Ring Spanner</u>	50.2PSR	2"
<u>FACOM 50.2P1/16SR - 2.1/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P1/16SR	2.1/16"
<u>FACOM 50.2P3/16SR - 2.3/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P3/16SR	2.3/16"

PRODUCT NAME	CODE	SIZE
<u>FACOM 50.2P13/64SR - 2.13/64"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P13/64SR	2.13/64"
<u>FACOM 50.2P3/8SR - 2.3/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P3/8SR	2.3/8"
<u>FACOM 50.2P9/16SR - 2.9/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P9/16SR	2.9/16"
<u>FACOM 50.2P5/8SR - 2.5/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P5/8SR	2.5/8"
<u>FACOM 50.2P3/4SR - 2.3/4"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P3/4SR	2.3/4"
<u>FACOM 50.2P15/16SR - 2.15/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.2P15/16SR	2.15/16"
<u>FACOM 50.3PSR - 3" Non-Sparking Inch Impact Slogging Ring Spanner</u>	50.3PSR	3"
<u>FACOM 50.3P1/8SR - 3.1/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.3P1/8SR	3.1/8"
<u>FACOM 50.3P3/8SR - 3.3/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.3P3/8SR	3.3/8"
<u>FACOM 50.3P9/16SR - 3.9/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.3P9/16SR	3.9/16"
<u>FACOM 50.3P3/4SR - 3.3/4"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.3P3/4SR	3.3/4"

PRODUCT NAME	CODE	SIZE
<u>FACOM 50.3P15/16SR - 3.15/16"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.3P15/16SR	3.15/16"
<u>FACOM 50.4P1/8SR - 4.1/8"</u> <u>Non-Sparking Inch Impact</u> <u>Slogging Ring Spanner</u>	50.4P1/8SR	4.1/8"

DESCRIPTION

FACOM 50.XSRU - Non-Sparking Inch Impact Slogging Ring Spanner

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Inch sizes - 11/16 - 4"1/8

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions