



FACOM 440.XSRM - Non-Sparking Metric Combination Spanner

440.6SR, 440.7SR, 440.8SR, 440.9SR, 440.10SR, 440.11SR, 440.12SR, 440.13SR, 440.14SR, 440.15SR, 440.16SR, 440.17SR, 440.18SR, 440.19SR, 440.20SR, 440.21SR, 440.22SR, 440.23SR, 440.24SR, 440.25SR, 440.26SR, 440.27SR, 440.30SR, 440.32SR, 440.34SR, 440.35SR, 440.36SR, 440.38SR, 440.41SR, 440.46SR, 440.50SR, 440.55SR, 440.60SR, 440.65SR, 440.70SR

PRODUCT NAME	CODE	SIZE
FACOM 440.6SR - 6mm Non-Sparking Metric Combination Spanner	440.6SR	6mm
FACOM 440.7SR - 7mm Non-Sparking Metric Combination Spanner	440.7SR	7mm
FACOM 440.8SR - 8mm Non-Sparking Metric Combination Spanner	440.8SR	8mm
FACOM 440.9SR - 9mm Non-Sparking Metric Combination Spanner	440.9SR	9mm
FACOM 440.10SR - 10mm Non-Sparking Metric Combination Spanner	440.10SR	10mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.11SR - 11mm Non-Sparking Metric Combination Spanner</u>	440.11SR	11mm
<u>FACOM 440.12SR - 12mm Non-Sparking Metric Combination Spanner</u>	440.12SR	12mm
<u>FACOM 440.13SR - 13mm Non-Sparking Metric Combination Spanner</u>	440.13SR	13mm
<u>FACOM 440.14SR - 14mm Non-Sparking Metric Combination Spanner</u>	440.14SR	14mm
<u>FACOM 440.15SR - 15mm Non-Sparking Metric Combination Spanner</u>	440.15SR	15mm
<u>FACOM 440.16SR - 16mm Non-Sparking Metric Combination Spanner</u>	440.16SR	16mm
<u>FACOM 440.17SR - 17mm Non-Sparking Metric Combination Spanner</u>	440.17SR	17mm
<u>FACOM 440.18SR - 18mm Non-Sparking Metric Combination Spanner</u>	440.18SR	18mm
<u>FACOM 440.19SR - 19mm Non-Sparking Metric Combination Spanner</u>	440.19SR	19mm
<u>FACOM 440.20SR - 20mm Non-Sparking Metric Combination Spanner</u>	440.20SR	20mm
<u>FACOM 440.21SR - 21mm Non-Sparking Metric Combination Spanner</u>	440.21SR	21mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.22SR - 22mm Non-Sparking Metric Combination Spanner</u>	440.22SR	22mm
<u>FACOM 440.23SR - 23mm Non-Sparking Metric Combination Spanner</u>	440.23SR	23mm
<u>FACOM 440.24SR - 24mm Non-Sparking Metric Combination Spanner</u>	440.24SR	24mm
<u>FACOM 440.25SR - 25mm Non-Sparking Metric Combination Spanner</u>	440.25SR	25mm
<u>FACOM 440.26SR - 26mm Non-Sparking Metric Combination Spanner</u>	440.26SR	26mm
<u>FACOM 440.27SR - 27mm Non-Sparking Metric Combination Spanner</u>	440.27SR	27mm
<u>FACOM 440.30SR - 30mm Non-Sparking Metric Combination Spanner</u>	440.30SR	30mm
<u>FACOM 440.32SR - 32mm Non-Sparking Metric Combination Spanner</u>	440.32SR	32mm
<u>FACOM 440.34SR - 34mm Non-Sparking Metric Combination Spanner</u>	440.34SR	34mm
<u>FACOM 440.35SR - 35mm Non-Sparking Metric Combination Spanner</u>	440.35SR	35mm
<u>FACOM 440.36SR - 36mm Non-Sparking Metric Combination Spanner</u>	440.36SR	36mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.38SR - 38mm Non-Sparking Metric Combination Spanner</u>	440.38SR	38mm
<u>FACOM 440.41SR - 41mm Non-Sparking Metric Combination Spanner</u>	440.41SR	41mm
<u>FACOM 440.46SR - 46mm Non-Sparking Metric Combination Spanner</u>	440.46SR	46mm
<u>FACOM 440.50SR - 50mm Non-Sparking Metric Combination Spanner</u>	440.50SR	50mm
<u>FACOM 440.55SR - 55mm Non-Sparking Metric Combination Spanner</u>	440.55SR	55mm
<u>FACOM 440.60SR - 60mm Non-Sparking Metric Combination Spanner</u>	440.60SR	60mm
<u>FACOM 440.65SR - 65mm Non-Sparking Metric Combination Spanner</u>	440.65SR	65mm
<u>FACOM 440.70SR - 70mm Non-Sparking Metric Combination Spanner</u>	440.70SR	70mm

DESCRIPTION

FACOM 440.XSRM - Non-Sparking Metric Combination Spanner

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Metric sizes - 6 - 70mm

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions