



FACOM ATWXCK - Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver



ATW4X100CK, ATWH5.5X125CK, ATWH6.5X150CK, ATWH8X175CK, ATWH10X175CK, ATWH12X200CK, ATWH14X250CK

PRODUCT NAME	CODE	SIZE
<u>FACOM ATW4X100CK - 4x100mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATW4X100CK	4x100mm
<u>FACOM ATWH5.5X125CK - 5.5x125mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH5.5X125CK	5.5x125mm
<u>FACOM ATWH6.5X150CK - 6.5x150mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH6.5X150CK	6.5x150mm
<u>FACOM ATWH8X175CK - 8x175mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH8X175CK	8x175mm

PRODUCT NAME	CODE	SIZE
<u>FACOM ATWH10X175CK - 10x175mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH10X175CK	10x175mm
<u>FACOM ATWH12X200CK - 12x200mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH12X200CK	12x200mm
<u>FACOM ATWH14X250CK - 14x250mm Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver</u>	ATWH14X250CK	14x250mm

DESCRIPTION

FACOM ATWXCK - Flared Slotted Protwist Shock Bolster Hex Bar Screwdriver

Features

- Impact zone with steel strike - hexagonal blade with 73MO steel
- Hexagonal blade with shoulder to take a wrench
- Extra-long blade for use in confined spaces
- Inline hardening process +100% tip life and +100% bar strength
- Handle material - softer for more comfort and still chemical resistant
- Golden electroplated Tip - 4x corrosion resistance
- Handle Channel +10% torque
- Laser marking - gives virtually permanent marking
- CNC tip machining - gives better screw fit increasing torque transfer and reducing wear

Technical Conformity

NF ISO 2380-1 - NF ISO 2380-2 - ISO 2380-1 - ISO 2380-2 - DIN ISO 2380-1 - DIN ISO 2380-2 -
ASME B107.600