



FACOM ATFX - Flared Slotted Protwist Screwdriver



ATF5.5X100, ATF5.5X150, ATF6.5X100, ATF6.5X150, ATF8X150
, ATF8X200, ATF10X200, ATF10X250

PRODUCT NAME	CODE	SIZE
FACOM ATF5.5X100 - 5.5x100mm Flared Slotted Protwist Screwdriver	ATF5.5X100	5.5x100mm
FACOM ATF5.5X150 - 5.5x150mm Flared Slotted Protwist Screwdriver	ATF5.5X150	5.5x150mm
FACOM ATF6.5X100 - 6.5x100mm Flared Slotted Protwist Screwdriver	ATF6.5X100	6.5x100mm
FACOM ATF6.5X150 - 6.5x150mm Flared Slotted Protwist Screwdriver	ATF6.5X150	6.5x150mm
FACOM ATF8X150 - 8x150mm Flared Slotted Protwist Screwdriver	ATF8X150	8x150mm

PRODUCT NAME	CODE	SIZE
<u>FACOM ATF8X200 - 8x200mm</u> <u>Flared Slotted Protwist</u> <u>Screwdriver</u>	ATF8X200	8x200mm
<u>FACOM ATF10X200 - 10x200mm</u> <u>Flared Slotted Protwist</u> <u>Screwdriver</u>	ATF10X200	10x200mm
<u>FACOM ATF10X250 - 10x250mm</u> <u>Flared Slotted Protwist</u> <u>Screwdriver</u>	ATF10X250	10x250mm

DESCRIPTION

FACOM ATFX - Flared Slotted Protwist Screwdriver

Features

- Forged blade with excellent tip fibre for high torsion strength
- Extra-long shank up to 250mm for difficult and remote access
- Inline hardening process +100% tip life and +100% bar strength
- Handle material - softer for more comfort and still chemical resistant
- Blade tri-coating treatment (Zinc-Nickel-Chromium)
- 4x Corrosion Resistance
- Handle Channel +10% torque
- Laser Marking - gives virtually permanent marking
- CNC tip machining - gives better screw fit increasing torque transfer and reducing wear

Technical Conformity

NF ISO 2380-1 - NF ISO 2380-2 - ISO 2380-1 - ISO 2380-2 - DIN ISO 2380-1 - DIN ISO 2380-2 -
ASME B107.600