



FACOM 440.XU - Inch Combination Spanner



440.1/4, 440.5/16, 440.11/32, 440.3/8, 440.7/16, 440.1/2, 440.9/16, 440.5/8, 440.11/16, 440.3/4, 440.13/16, 440.7/8, 440.15/16, 440.1P, 440.1P1/16, 440.1P1/8, 440.1P1/4, 440.1P5/16, 440.1P3/8, 440.1P7/16, 440.1P1/2

PRODUCT NAME	CODE	SIZE
FACOM 440.1/4 - 1/4" Inch Combination Spanner	440.1/4	1/4"
FACOM 440.5/16 - 5/16" Inch Combination Spanner	440.5/16	5/16"
FACOM 440.11/32 - 11/32" Inch Combination Spanner	440.11/32	11/32"
FACOM 440.3/8 - 3/8" Inch Combination Spanner	440.3/8	3/8"
FACOM 440.7/16 - 7/16" Inch Combination Spanner	440.7/16	7/16"
FACOM 440.1/2 - 1/2" Inch Combination Spanner	440.1/2	1/2"
FACOM 440.9/16 - 9/16" Inch Combination Spanner	440.9/16	9/16"

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.5/8 - 5/8" Inch Combination Spanner</u>	440.5/8	5/8"
<u>FACOM 440.11/16 - 11/16" Inch Combination Spanner</u>	440.11/16	11/16"
<u>FACOM 440.3/4 - 3/4" Inch Combination Spanner</u>	440.3/4	3/4"
<u>FACOM 440.13/16 - 13/16" Inch Combination Spanner</u>	440.13/16	13/16"
<u>FACOM 440.7/8 - 7/8" Inch Combination Spanner</u>	440.7/8	7/8"
<u>FACOM 440.15/16 - 15/16" Inch Combination Spanner</u>	440.15/16	15/16"
<u>FACOM 440.1P - 1" Inch Combination Spanner</u>	440.1P	1"
<u>FACOM 440.1P1/16 - 1.1/16" Inch Combination Spanner</u>	440.1P1/16	1.1/16"
<u>FACOM 440.1P1/8 - 1.1/8" Inch Combination Spanner</u>	440.1P1/8	1.1/8"
<u>FACOM 440.1P1/4 - 1.1/4" Inch Combination Spanner</u>	440.1P1/4	1.1/4"
<u>FACOM 440.1P5/16 - 1.5/16" Inch Combination Spanner</u>	440.1P5/16	1.5/16"
<u>FACOM 440.1P3/8 - 1.3/8" Inch Combination Spanner</u>	440.1P3/8	1.3/8"
<u>FACOM 440.1P7/16 - 1.7/16" Inch Combination Spanner</u>	440.1P7/16	1.7/16"
<u>FACOM 440.1P1/2 - 1.1/2" Inch Combination Spanner</u>	440.1P1/2	1.1/2"

DESCRIPTION

FACOM 440.XU - Inch Combination Spanner

Features

Standard wrench for all common applications

High mechanical performance combined with compact design complying with aeronautical standards

Ring head

Ring clearance (E dimension) designed for better access to serial-mounted or embedded screws

OGV profile 12-point ring for powerful tightening while protecting the nut

Suffix H - 6 sided ring

Ring head with 15° angle

Open end head

Open end with 15° angle

Open end head-handle geometry optimised for increased accessibility

Inch sizes - 1/4 - 1-1/2

Satin chrome finish

Technical Conformity

ASME B107.100 - SAE AS954G

Extra Information

The 440 combination wrench was designed to combine compactness with strength

Dimensions meet the requirements of tooling standards NF ISO 1711-1 and aerospace standard SAE

AS 954G

Tightening torques guaranteed significantly above specifications of high strength tooling and bolting standards ISO 898-1 (quality class 12.9)

The 440 combination wrench was also designed to ensure maximum user safety. When critical tightening torques are reached the wrench is distorted gradually

No brutal breaking likely to injure the user