



FACOM 440.XM - Metric Combination Spanner



440.4H, 440.5H, 440.5.5H, 440.6, 440.7, 440.8, 440.9, 440.10, 440.11, 440.12, 440.13, 440.14, 440.15, 440.16, 440.17, 440.18, 440.19, 440.20, 440.21, 440.22, 440.23, 440.24, 440.25, 440.26, 440.27, 440.28, 440.29, 440.30, 440.32, 440.33, 440.34, 440.35, 440.36, 440.38, 440.41

PRODUCT NAME	CODE	SIZE
FACOM 440.4H - 4mm Metric Combination Spanner	440.4H	4mm
FACOM 440.5H - 5mm Metric Combination Spanner	440.5H	5mm
FACOM 440.5.5H - 5.5mm Metric Combination Spanner	440.5.5H	5.5mm
FACOM 440.6 - 6mm Metric Combination Spanner	440.6	6mm
FACOM 440.7 - 7mm Metric Combination Spanner	440.7	7mm
FACOM 440.8 - 8mm Metric Combination Spanner	440.8	8mm
FACOM 440.9 - 9mm Metric Combination Spanner	440.9	9mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.10 - 10mm Metric Combination Spanner</u>	440.10	10mm
<u>FACOM 440.11 - 11mm Metric Combination Spanner</u>	440.11	11mm
<u>FACOM 440.12 - 12mm Metric Combination Spanner</u>	440.12	12mm
<u>FACOM 440.13 - 13mm Metric Combination Spanner</u>	440.13	13mm
<u>FACOM 440.14 - 14mm Metric Combination Spanner</u>	440.14	14mm
<u>FACOM 440.15 - 15mm Metric Combination Spanner</u>	440.15	15mm
<u>FACOM 440.16 - 16mm Metric Combination Spanner</u>	440.16	16mm
<u>FACOM 440.17 - 17mm Metric Combination Spanner</u>	440.17	17mm
<u>FACOM 440.18 - 18mm Metric Combination Spanner</u>	440.18	18mm
<u>FACOM 440.19 - 19mm Metric Combination Spanner</u>	440.19	19mm
<u>FACOM 440.20 - 20mm Metric Combination Spanner</u>	440.20	20mm
<u>FACOM 440.21 - 21mm Metric Combination Spanner</u>	440.21	21mm
<u>FACOM 440.22 - 22mm Metric Combination Spanner</u>	440.22	22mm
<u>FACOM 440.23 - 23mm Metric Combination Spanner</u>	440.23	23mm
<u>FACOM 440.24 - 24mm Metric Combination Spanner</u>	440.24	24mm

PRODUCT NAME	CODE	SIZE
<u>FACOM 440.25 - 25mm Metric Combination Spanner</u>	440.25	25mm
<u>FACOM 440.26 - 26mm Metric Combination Spanner</u>	440.26	26mm
<u>FACOM 440.27 - 27mm Metric Combination Spanner</u>	440.27	27mm
<u>FACOM 440.28 - 28mm Metric Combination Spanner</u>	440.28	28mm
<u>FACOM 440.29 - 29mm Metric Combination Spanner</u>	440.29	29mm
<u>FACOM 440.30 - 30mm Metric Combination Spanner</u>	440.30	30mm
<u>FACOM 440.32 - 32mm Metric Combination Spanner</u>	440.32	32mm
<u>FACOM 440.33 - 33mm Metric Combination Spanner</u>	440.33	33mm
<u>FACOM 440.34 - 34mm Metric Combination Spanner</u>	440.34	34mm
<u>FACOM 440.35 - 35mm Metric Combination Spanner</u>	440.35	35mm
<u>FACOM 440.36 - 36mm Metric Combination Spanner</u>	440.36	36mm
<u>FACOM 440.38 - 38mm Metric Combination Spanner</u>	440.38	38mm
<u>FACOM 440.41 - 41mm Metric Combination Spanner</u>	440.41	41mm

DESCRIPTION

FACOM 440.XM - Metric Combination Spanner

Features

Standard wrench for all common applications

High mechanical performance combined with compact design complying with aeronautical standards

Ring head

Ring clearance (E dimension) designed for better access to serial-mounted or embedded screws

OGV profile 12-point ring for powerful tightening while protecting the nut

Suffix H - 6 sided ring

Ring head with 15° angle

Open end head

Open end with 15° angle

Open end head-handle geometry optimised for increased accessibility

Metric dimensions - 4 - 41mm

Satin chrome finish

Technical Conformity

NF ISO 691 - NF ISO 7738 - NF ISO 3318 - NF ISO 1711-1 - E74-306 - ISO 691 - ISO 7738 - ISO 3318
- ISO 1711-1 - DIN ISO 691 - DIN 1711-1 - DIN 3113 - ASME B107.100

Extra Information

The 440 combination wrench was designed to combine compactness with strength

Dimensions meet the requirements of tooling standards NF ISO 1711-1 and aerospace standard SAE

AS 954G

Tightening torques guaranteed significantly above specifications of high strength tooling and bolting standards ISO 898-1 (quality class 12.9)

The 440 combination wrench was also designed to ensure maximum user safety. When critical tightening torques are reached the wrench is distorted gradually

No brutal breaking likely to injure the user