



FACOM K.XSRU - Non-Sparking 3/4" Square Drive Inch 12pt Socket

K.1P1/8SR, K.1P3/16SR, K.1P5/16SR, K.1P3/8SR, K.1P7/16SR, K.1P5/8SR, K.1P3/4SR, K.1P13/16SR, K.1P7/8SR, K.2PSR

PRODUCT NAME	CODE	SIZE
FACOM K.1P1/8SR - 1.1/8" Non-Sparking 3/4" Square Drive Inch 12pt Socket	K.1P1/8SR	1.1/8"
FACOM K.1P3/16SR - 1.3/16" Non-Sparking 3/4" Square Drive Inch 12pt Socket	K.1P3/16SR	1.3/16"
FACOM K.1P5/16SR - 1.5/16" Non-Sparking 3/4" Square Drive Inch 12pt Socket	K.1P5/16SR	1.5/16"
FACOM K.1P3/8SR - 1.3/8" Non-Sparking 3/4" Square Drive Inch 12pt Socket	K.1P3/8SR	1.3/8"
FACOM K.1P7/16SR - 1.7/16" Non-Sparking 3/4" Square Drive Inch 12pt Socket	K.1P7/16SR	1.7/16"

PRODUCT NAME	CODE	SIZE
<u>FACOM K.1P5/8SR - 1.5/8" Non-Sparking 3/4" Square Drive Inch 12pt Socket</u>	K.1P5/8SR	1.5/8"
<u>FACOM K.1P3/4SR - 1.3/4" Non-Sparking 3/4" Square Drive Inch 12pt Socket</u>	K.1P3/4SR	1.3/4"
<u>FACOM K.1P13/16SR - 1.13/16" Non-Sparking 3/4" Square Drive Inch 12pt Socket</u>	K.1P13/16SR	1.13/16"
<u>FACOM K.1P7/8SR - 1.7/8" Non-Sparking 3/4" Square Drive Inch 12pt Socket</u>	K.1P7/8SR	1.7/8"
<u>FACOM K.2PSR - 2" Non-Sparking 3/4" Square Drive Inch 12pt Socket</u>	K.2PSR	2"

DESCRIPTION

FACOM K.XSRU - Non-Sparking 3/4" Square Drive Inch 12pt Socket

Features

Special non sparking and anti-magnetic Copper-Beryllium alloy

Drive - 3/4"

Metric sizes - 1.1/8 - 2"

FACOM has determined the composition of the Cu-Be alloy as well as its specific treatment according to the use of each tool

In addition to its non sparking properties the Cu-Be alloy is also anti-magnetic and highly corrosion resistant

Having a lower density it also significantly reduces user fatigue

FACOM ADF tools have been designed in accordance with the most widely used dimensional standards or adapted to perform the tools main functions